



SAFETY DATA SHEET

SECTION I:	IDENTIFICATION
-------------------	-----------------------

Product names:	ProhmProtect 3000 Series
Other means of Identification:	Not available
Product type:	Conductive Paste and Lubricant
Manufacturer:	ProhmTECT 47108 276 th Street Harrisburg, SD 57032
Emergency phone #:	605-767-1200
Regulatory Information #:	605-767-1200

SECTION II:	HAZARD(S) IDENTIFICATION
--------------------	---------------------------------

Emergency Overview

Appearance/Odor: Silver metal and lubricant with little odor.

Potential Health Effects:

Acute Eye:

May cause irritation.

Acute Skin:

May cause irritation.

Acute Inhalation:

May be irritating to respiratory tract.

Acute ingestion:

Not considered a route of exposure under anticipated use conditions. May cause severe irritation and to the digestive tract if ingested.

Chronic Exposure:

Not determined

Aggravation of Pre-existing Conditions:

Not determined



SAFETY DATA SHEET

SECTION III: COMPOSITION/INFORMATION ON INGREDIANT

Component	CAS#
Stainless Steel	65997-19-5
Proprietary Lubricant A	Trade Secret
Proprietary Lubricant Grease	68611-44-9
Mineral Oil, Food Grade	8042-47-5

Petroleum hydrocarbon/metal mixture:

Three proprietary ingredients:

The identity of these chemicals constitutes a trade secret. To the best of Prohm-tect's knowledge, the product contains no SARA 313 in reportable amounts as of this date.

SECTION IV: FIRST-AID MEASURES

First Aid Measures for Accidental:

Eye Exposure:

Immediately flush eyes with copious amounts of water. If irritation develops, SEEK MEDICAL ATTENTION.

Skin Exposure:

Flood affected area with water for extended period then wash with soap. If irritation develops, seek medical attention.

Inhalation:

Remove to fresh air. Seek medical attention if breathing becomes difficult.

Ingestion:

Seek medical attention.



SAFETY DATA SHEET

SECTION V: FIRE-FIGHTING MEASURES

Fire Hazard Data:

For Lubricant

Autoignition: N/A

Flash Point: 350°F

Flammability Limits (vol/vol%):

Lower:

N/A

Upper:

N/A

Extinguishing Media:

Use extinguishing media suitable for surrounding fire

Special Fire Fighting Procedures:

Keep containers cool by spraying with water when exposed to fire; if flames have reached the product causing a possible decomposition yielding toxic compounds, use self-contained breathing apparatus. This product does not burn, but will thermally dissociate above 290°C.

Unusual Fire and Explosion Hazards:

Dissociate at temperatures above 290°C may cause the evolution of toxic gaseous fluorine compounds.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill:



SAFETY DATA SHEET

Vacuum or sweep up material and place in a suitable container for reclamation or disposal. Do not discharge into drains or sewers. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations.

SECTION VII: HANDLING AND STORAGE

Handling/Storage:

Avoid contact with skin and eyes. Keep in a tightly closed container, stored in a cool, dry, well ventilated area.

SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

Component	ACGIH	NIOSH	OSHA-PELs
Stainless Steel	0.1 mg/m ³	ND	0.01 mg/m ³
Lubricant	ND	ND	ND

Engineering Controls:

General mechanical ventilation is adequate for normal use. Local exhaust is recommended for confined areas.

Respiratory Protection:

None

Eye / Face Protection:

Use eye protection to protect eyes.

Skin Protection:

Use gloves to protect hands.



SAFETY DATA SHEET

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance: Silver metal with lubricant

Odor: Slight

pH: ND

For Lubricant

Specific Gravity: 1.1

Water Solubility: Insoluble

Melting Point: 2795 F

Freezing Point NA

Boiling Point: ND

Vapor Pressure: 10^{-7} @ 20C

Density: NA

Percent Volatiles by Volume:N/A

Evaporation Rate: ND

Viscosity: ND

Density: ND

SECTION X: STABILITY AND REACTIVITY

Chemical Stability:

Stable

Conditions to Avoid:

Avoid heating above 280°C.

Materials / Chemicals to Be Avoided:

Ammonia, acetylene, ethyl alcohol with nitric acid, hydrogen peroxide, oxalic acid. Molten alkali metals, interhalogen compounds, strong or not aqueous alkali and Lewis acids above 100°C.



SAFETY DATA SHEET

Hazardous Decomposition Products:

Toxic HF and COF₂ from thermal decomposition in air plus H₂O

Hazardous Polymerization:

Will not occur

SECTION XI: TOXICOLOGICAL INFORMATION
--

Acute Effects:

LD50 Oral:	ND
LD50 Dermal:	ND

Chronic Effects

Carcinogenicity:	ND
Mutagenicity:	ND
Reproductive Effects:	ND
Developmental Effects:	ND

SECTION XII: ECOLOGICAL INFORMATION
--

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

SECTION XIII: DISPOSAL CONSIDERATIONS
--

Waste Disposal Method:

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION XIV: TRANSPORTATION INFORMATION
--



SAFETY DATA SHEET

US Department of Transportation Shipping Name:

US Department of Transportation	Proper Shipping Name	Not Regulated
	Hazard Class	Not Regulated
	ID Number	Not Regulated
	Packaging Group	Not Regulated

SECTION XV: REGULATORY INFORMATION

Federal Regulations:

SARA Title III Hazard Classes:

Fire Hazard: No
 Reactive Hazard: No

Release of Pressure: No

Acute Health Hazard: No

Chronic Health Hazard: No

TSCA:

All components of this product are on the TSCA inventory or are exempt from TSCA Inventory requirements

Other Regulations:

None

SECTION XVI: OTHER INFORMATION

National Paint & Coating Hazardous Materials Identification System – HMIS(R):

Health Hazard: 1
 Flammability: 0
 Reactivity: 0

Key Legend Information:

NA – Not Applicable

ND – Not Determined

ACGIH – American Conference of Governmental Industrial Hygienists



SAFETY DATA SHEET

OSHA – Occupational Safety and Health Administration

TLV – Threshold Limit Value

PEL – Permissible Exposure Limit

TWA – Time Weighted Average

STEL – Short Term Exposure Limit

NTP – National Toxicology Program

IARC – International Agency for Research Cancer